

# METZ PT POWDER



## DESCRIPTION:

Metz PT Powder is a ready to use inert white powder that is made of highly fibrillated HDPE (high density Polyethylene) fibres. This can be used in many Metz coatings, adhesives, caulks, sealants and cementitious flooring products to help prevent sagging.

---

## FEATURES AND BENEFITS:

- Improves suspension of pigments and fillers
  - Improves water resistance
  - Improves flexibility, reducing cracking
  - Improves sag resistance
  - **Quality Accreditation**  
The management system governing the development and manufacture of this product is proudly ISO9001:2015 certified.
  - Does not absorb water or binders
  - Provides texture
  - Only required to be added in small quantities
- 

## RECOMMENDED:

This product can be used as an effective thickening agent to improve anti-sagging properties in many Metz materials.

---

## PHYSICAL PROPERTIES: (Typical Values)

Specific Gravity: 0.96 g/cm<sup>3</sup>

Maximum Service Temperature: 120°C

*Note:* this may reduce the service temperature of the Metz host material

---

## USAGE:

Up to 2% by weight of host Metz product as required.

---

## INSTRUCTIONS FOR USE:

Add to Liquid or Powder component as required up to a maximum of 2% by weight.

Avoid excessive or aggressive mixing as this can reduce effectiveness of Metz PT.

Mix thoroughly ensuring all powder remains suspended and not on the surface.

Wear safety eye glasses, dust protective masks and appropriate gloves while handling and mixing. Refer Metz SDS for details.

*Note:* Ensure you have the latest mixing instructions, refer [www.metz.net.au](http://www.metz.net.au)

---

## STORAGE/SHELF LIFE:

Store in cool, dry conditions protected from humidity. Under these conditions minimum shelf life is 24 months.



