

# METZ MASKING COMPOUND



## DESCRIPTION:

Metz Masking Compound is a water based coating which is applied to ceramic tiles prior to grouting.

---

## FEATURES AND BENEFITS:

- **Protects Tile Face**  
Prevents the absorption of grouting compound into the tile surface, thus preventing staining.
  - **Easy Application**  
May be applied with brush or roller.
  - **Easy Clean Up**  
After grout has hardened, scrub with water for easy removal.
- 

## RECOMMENDED:

Using Metz Masking Compound when grouting with METZ 5NF, 6NF, 12P, 12P-2 Part, 12PHF and 15VE. Please refer to appropriate data sheet.

Suitable for use with Metz Sicodur® and Metz Europave® abrasive tiles.

---

## NOT RECOMMENDED:

On tiles with very rough or profiled surfaces - WAX before laying.

---

## COVERAGE:

Theoretical quantity (allow for wastage)

Dependent on tile porosity                      10 sq. metre/litre per coat

---

## INSTRUCTIONS FOR USE:

### Application:

Tile surfaces must be clean and dry. Apply Metz Masking Compound sparingly with a lambswool roller in thin coats, taking great care to ensure that it does not run down the sides of the joints. At least two coats of Metz Masking Compound should be applied, ensuring that the first coat is completely dry before applying the second coat. (Drying time approximately 1-2 hours under normal conditions). If porous tiles are used, it is recommended that three or more coats be applied.

### Note:

If tile surfaces are very rough, it is recommended that they be waxed prior to laying.

Rollers can be cleaned with water.

### Cleaning Off:

After the grout has cured, the Metz Masking Compound and grout residue can be removed with water and a scrubbing machine. If using a scrubbing machine use soft bristles or a white (softest) pad only.

### Storage:

Store in original containers in cool dry place. Under these conditions minimum shelf life is 12 months.

---

## SAFETY PRECAUTIONS:

Metz Masking Compound is classified as non-hazardous. General precautions for handling chemical products should be followed.

For full safety precautions refer to the Safety Data Sheet.



Acid Protection • Industrial Flooring • Specialty Ceramic Tiling

## NOTES


**Always ensure you have the latest data sheet version, refer www.metz.net.au**

- 1. The customer must comply strictly with the instructions contained in this product data sheet. Metz is not responsible for any advice or variations to this data sheet which are not confirmed in writing.
- 2. If the customer has a claim against Metz in respect of any product supplied to the customer by Metz whether due to a fault in the product or the negligence or breach of contract by Metz or for any other reason:
  - a) Metz shall not be liable for any loss of damage including consequential loss or damage or loss of profits arising thereby;
  - b) Metz may at its option replace the defective product free of charge to the customer or refund all payments made to it by the buyer in respect of the defective product; and the maximum liability of Metz shall be the cost of replacing the defective product.

REV 07/20

**METZ SPECIALTY MATERIALS PTY LTD**  
A.C.N. 140 636 639  
 15A Stanton Road, Seven Hills, NSW 2147  
 Facsimile: (02) 9671 4292 Phone: (02) 9671 1311  
 6 University Place, Clayton North, VIC 3168  
 Facsimile: (03) 9561 6944 Phone: (03) 9561 6144  
 Unit 16, 42 Smith Street, Capalaba QLD 4157  
 Facsimile: (07) 3823 5552 Phone: (07) 3823 5555

**Distributor**